



“yol güvenliđi”

2023

Ürün Katalođu

Trafik Güvenlik Sistemleri

EVELUX / SEKTÖREL MİSYON

Hızla artan araç ve yaya trafiğinde emniyet ve düzeni sağlamak kaçınılmaz bir ihtiyaç haline geliyor. Bu bilinçle ortaya çıkan Evelux'e sektörün ihtiyaçları daima esin kaynağı oldu. Evelux "tasarımda işlevsellik", "üretimde kalite" ve "teslimatta güven" ilkeleriyle başarısını lider konumunda arttırarak ilerlemiştir.

EVELUX / FONKSİYONEL YOL GÜVENLİĞİ

Araç ve yaya trafiğinde emniyet ve düzeni sağlamak, özel ve kamu kurumlarından kişilere kadar yönetilebilir olabilmek. Bu amaçla kullanılan ürünlerin ve sistemlerin pratik olduğu kadar işlevsel olmasında önemlidir. Evelux, her tasarımda ürünlerine pratik uzantılar ekleyerek fonksiyonel yol güvenliği sağlayan sistemleri üretmektedir.



EVELUX / SECTORAL MISSION














It becomes an inevitable need to provide safety and order in rapidly increasing vehicles and pedestrian traffic. Evelux which set out with this consciousness, always took inspiration from the necessity of the sector. With its principles which are “functionality in design”, “quality in production” and “trust in delivery”, Evelux has advanced by increasing its success in its leading position.
























EVELUX / FUNCTIONAL ROAD SAFETY

Providing safety and order in vehicle and pedestrian traffic, to become manageable from private and public institutions to individuals. It is also important that the products and systems used for this purposes are functional as well as practical. Evelux, manufactures systems that provide functional road safety by adding practical extensions to its products in every design.



/Index/

	Plastic Road Barriers	06
	Metal Safety Barrier	06
	Plastic Safety Barriers	07
	Foldable Traffic Sign Barricades	08
	Foldable Sign Delineators	09
	Traffic Sign Boards	09
	Traffic Sign Barricades	10
	Channelizer Posts	11
	Solar Flasher LED Lamps	12
	Solar Flasher LED Lamps	13
	Solar/AC Flasher LED Lamps & Signs	13
	AC Flashing LED Road Signs	13
	Solar Flashing LED Road Maintenance Signs	14
	Solar Flashing LED Road Warning Signs	14
	Solar Flashing LED Road Maintenance Signs	15
	90 cm PVC / TPE Cones	16
	75-50 cm PVC / TPE Cones	16
	70-52 cm PVC / TPE Cones	17
	90-50-32 cm PVC Cones / 32 cm TPE Cones	17
	PPC Cones / Sign Board Cones	18
	Pavement Signs & Foldable Floor Sign	18
	Traffic Island Bollards	19
	Flexible Removable Delineators	19
	TPU Flexible Delineators With Socket	19
	TPU Flexible Delineators	20
	TPE Flexible Delineators	21

	Channelizers with Delineator	22
	Channelizers with Flap & Flexible Delineator Boards	22
	Channelizers with Flap & Cat Eyes	23
	Channellizer Curbs	23
	Channellizers with Solar Flasher & Cat Eye	23
	Road Markers with Solar Flasher	24
	Road Markers with Reflector / Cat Eyes	24
	PVC Speed Ramps with Reflective Tapes	25
	PVC Speed Ramps with Reflector	25
	PPC Speed Bumps with Reflector	25
	PPC Speed Bumps with Solar Flasher	25
	PPC Speed Bumps with Cat Eyes	25
	Car Parking Stoppers	26
	Spike Barrier	26
	Corner Guards	27
	Traffic Safety Mirrors	27
	Centrum Bollards	28
	Flexible Centrum Bollards / Ensign Centrum Bollards	28
	Centrum Bollards / Buffer & Steel Bollards	29
	Cable Protector Ramp	29
	Tactile Floor Indicators	30
	Reflective Sheeting Materials / Reflective Tapes	31
	Plastic Boards	32
	Plastic Sign Boards	32
	Evelux Adaptors	33
	Barricade Accesories / Fixing Screws	33



12520 FB R



12526 FB R

Plastic Road Barriers

Reflective Engineer Grade

	PART No.	DESCRIPTIONS
	12520 FB R	plastic road barrier with cat eyes - (HxLxW)60x100x40cm material: PPC / weight: 20.0 kg
	12526 FB R	plastic road barrier with solar flasher - (HxLxW)60x100x40cm material:PPC / weight: 20.0kg



12524 FB R




12522 FB R

Plastic Road Barriers

Reflective High Intensity Grade

	PART No.	DESCRIPTIONS
	12524 FB R	plastic road barrier with delineator - (HxLxW)100x100x40cm del.:(HxØ)40 cmx80 mm / material:PPC / weight: 20.0 kg
	12522 FB R	plastic road barrier with flap - (HxLxW) 120x100x40cm sign: (HxW) 50x12 cm / material: PPC / weight: 20.0 kg




12535 FB ST

Metal Safety Barrier

	PART No.	DESCRIPTIONS
	12535 FB ST	metal safety barrier - (HxL) 120x200 cm material: metal - Ø32x2 mm round tube / weight: 15.5 kg

Crowd Barrier


versatile application, as barrier and security of event sites, welded galvanized steel construction of Ø 32 mm round tube, hooks and connection brackets are welded to the sides for combining several elements, two feet of bent round tube provide stability of barrier, total height: 1.20 m, sturdy vertical bars of Ø 16 mm round tube provide safe barrier action



Plastic Safety Barrier

Reflective Engineer Grade

	PART No.	DESCRIPTIONS
	12511 FB R	plastic safety barrier - (HxL) 100x150 cm material: PPC / weight: 10.5 kg



12511 FB R

ACCESSORIES



Plastic Safety Barriers

Reflective Engineer Grade

	PART No.	DESCRIPTIONS
	12510 FB R	plastic safety barrier - (HxL) 100x150 cm color: red / material: PPC / weight: 12.0 kg
	12514 FB R	plastic safety barrier - (HxL) 100x150 cm color: yellow / material: PPC / weight: 12.0 kg
	12518 FB R	plastic safety barrier - (HxL) 100x150 cm color: white / material: PPC / weight: 12.0 kg



12510 FB R

ACCESSORIES



Plastic Sign Barrier

Reflective Engineer Grade

	PART No.	DESCRIPTIONS
	12513 FB R	plastic sign barrier - (HxL) 100x150 cm sign board: 100x50 cm / material:PPC / weight:12.3 kg




12513 FB R

ACCESSORIES



Alternative 1



Alternative 2



12500 FB R




ACCESSORIES



Foldable Traffic Sign Barricade
Reflective Engineer Grade

	PART No.	DESCRIPTIONS
	12500 FB R	foldable traffic sign barricade - (HxW) 150x105 cm sign board: 90x90 cm / material: PPC / weight: 18.0 kg



12501 FB R




12503 FB R

ACCESSORIES



Foldable Traffic Sign Barricades
Reflective Engineer Grade

	PART No.	DESCRIPTIONS
	12501 FB R	foldable traffic sign barricade - (HxW) 90x115 cm sign board: 30x90 cm / material: PPC / weight: 20.0 kg
	12503 FB R	foldable traffic sign barricade - (HxW) 110x55 cm sign board: 90x30 cm / material: PPC / weight: 15.5 kg



12504 FB R

ACCESSORIES



Foldable Traffic Sign Barricade
Reflective Engineer Grade

	PART No.	DESCRIPTIONS
	12504 FB R	foldable traffic sign barricade - (HxW) 110x250 cm sign board: 125x75 cm / material: PPC / weight: 37.0 kg



Foldable Traffic Sign Board

Reflective Engineer Grade

	PART No.	DESCRIPTIONS
	12417 DB R	foldable traffic sign board - (HxW) 90x60 cm sign board: 60x60 cm / material: PPC / weight: 12.0 kg



12417 DB R




ACCESSORIES



Foldable Sign Delineators

Reflective Engineer Grade

	PART No.	DESCRIPTIONS
	12410 DB R	foldable sign delineator - (H) 120 cm / base: 32x48 cm sign board: 100x25 cm / material: PPC / weight: 12.0 kg
	12415 DB R	foldable sign delineator - (H) 104 cm / base: 32x48 cm sign board: 80x20 cm / material: PPC / weight: 11.0 kg
	12416 DB R	foldable sign delineator - (H) 72 cm / base: 22x45 cm sign board: 48x20 cm / material: PPC / weight: 6.5 kg



12416 DB R

12415 DB R

12410 DB R

12410 DB R / ACCESSORIES



Traffic Sign Boards

Reflective Engineer Grade

	PART No.	DESCRIPTIONS
	12425 DB R A	traffic sign board - (HxW) 90x49 cm sign board: 60x40 cm / material: PPC / weight: 7.5 kg
	12423 DB R A	traffic sign board - (HxW) 90x49 cm sign board: 60x40 cm / material: PPC / weight: 7.5 kg




12423 DB R A



12425 DB R A

12423-12425 DB R A / ACCESSORIES






12405 DB R

ACCESSORIES



Traffic Sign Barricade
Reflective Engineer Grade

	PART No.	DESCRIPTIONS
	12405 DB R	traffic sign barricade - (HxL) 120x180 cm sign board: 75x125 cm / material: PPC / weight: 31.0 kg



12407 DB R

ACCESSORIES



Traffic Sign Barricade
Reflective Engineer Grade


	PART No.	DESCRIPTIONS
	12407 DB R	traffic sign barricade - (HxL) 120x180 cm sign board: 31.5x90 cm / material: PPC / weight: 27.0 kg



Channelizer Posts

Reflective Engineer Grade


	PART No.	DESCRIPTIONS
	12404 DB R	channelizer post - (HxØ) 120 cm x 110 mm base:(Ø)400 mm / material:PPC / weight:12.0 kg
	12414 DB R	channelizer post - (HxØ) 120 cm x 110 mm base:(Ø)400 mm / material:PPC / weight:12.0 kg



Channelizer Posts & Cone

Reflective Engineer Grade

	PART No.	DESCRIPTIONS
	12420 DB R	channelizer post - (HxØ) 110 cm x 80 mm base:(Ø)400 mm / material:PPC / weight:6.5 kg
	12422 DB R	channelizer post - (HxØ) 110 cm x 80 mm base:(Ø)400 mm / material:PPC / weight:6.5 kg
	12430 DB R	channelizer cone - (HxØ) 120 cm x 140 mm base:(Ø) 450 mm / material: PPC / weight: 8.7 kg



Channelizer Posts

Reflective Engineer Grade

	PART No.	DESCRIPTIONS
	12403-1 DB R	channelizer post - (HxØ) 100 cm x 63 mm base:(Ø)400 mm / material: PPC / weight: 4.0 kg
	12409-1 DB R	channelizer post - (HxØ) 100 cm x 63 mm base:(Ø)400 mm / material: PPC / weight: 4.0 kg
	12435 DB	channelizer post - (HxØ) 90 cmx40 mm base:(Ø) 300 mm / material: PE / weight: 1.9 kg



12435 DB / 12403-1 DB R / 12409 -1 DB R / ACCESSORIES



Solar Flasher Led Lamps



11811 FL S



11813 FL K

ACCESSORIES



	PART No.	DESCRIPTIONS
	11811 FL S	solar flasher led lamp - (HxW) 30x24 cm - yellow leds flash lens: Ø160 mm / material: ABS / weight: 0.84 kg
	11813 FL K	solar flasher led lamp - (HxW) 30x24 cm - red leds flash lens: Ø160 mm / material: ABS / weight: 0.84 kg

ELECTRONIC SPECS.

solar panel	type	monocrystalline silicon cell	LED	color	Yellow Red
	dimension (H/L)	45x120 mm		dimension	Ø 5 mm leds
	voltage	4 V		flash rate	105 f/min
	watt	0.6 W		visibility dist.	200 m (night)
rechargeable battery	material	Ni-MH		operation time	whole night/ daily sunlight
	voltage	2x1.2 V		operation temp.	-20°C/+60°C
rechargeable battery	current	2000 mA/h			

Solar Flasher Led Lamps



11825 FL S



11827 FL K

ACCESSORIES



	PART No.	DESCRIPTIONS
	11825 FL S	solar flasher led lamp - (HxW) 29x22 cm - yellow leds flash lens: Ø160 mm / material: ABS / weight: 0.75 kg
	11827 FL K	solar flasher led lamp - (HxW) 29x22 cm - red leds flash lens: Ø160 mm / material: ABS / weight: 0.75 kg

ELECTRONIC SPECS.

solar panel	type	monocrystalline silicon cell	LED	color	Yellow Red
	dimension (H/L)	45x120 mm		dimension	Ø 5 mm leds
	voltage	4 V		flash rate	105 f/min
	watt	0.6 W		visibility dist.	200 m (night)
rechargeable battery	material	Ni-MH		operation time	whole night/ daily sunlight
	voltage	2x1.2 V		operation temp.	-20°C/+60°C
rechargeable battery	current	2000 mA/h			

Solar Flasher Led Lamps



11814 FL S



11816 FL K



11817 FL K



11819 FL S



11821 FL M

ACCESSORIES




	PART No.	DESCRIPTIONS
	11814 FL S	solar flasher led lamp - (HxW) 27x22 cm - yellow leds flash lens: Ø160 mm / material: ABS / weight: 0.50 kg
	11816 FL K	solar flasher led lamp - (HxW) 27x22 cm - red leds flash lens: Ø160 mm / material: ABS / weight: 0.50 kg
	11817 FL K	solar flasher led lamp - (HxØ)14.5 cmx128 mm-red leds diameter flash: Ø120 mm / material: PC / weight: 0.35 kg
	11819 FL S	solar flasher led lamp-(HxØ)14.5 cmx128 mm-yellow leds diameter flash: Ø120 mm / material: PC / weight:0.35 kg
	11821 FL M	solar flasher led lamp - (HxØ)14.5 cmx128 mm-blue leds diameter flash: Ø120 mm / material: PC / weight:0.35 kg

ELECTRONIC SPECS.

solar panel	type	monocrystalline silicon cell	LED	color	Yellow Red
	dimension (H/L)	45*120-60*54mm		dimension	Ø 5 mm leds
	voltage	4 V - 3V		flash rate	105-115 f/min
	watt	0.6 - 0.4 W		visibility dist.	200-100 m(night)
rechargeable battery	material	Ni-MH		operation time	whole night/ daily sunlight
	voltage	1.2 V		operation temp.	-20°C/+60°C
rechargeable battery	current	2000 mA/h			

Solar Flasher Led Lamps

	PART No.	DESCRIPTIONS
	11851 FL S	solar flasher led lamp - yellow leds flash lens: Ø300 mm / material: PC / weight: 8.0 kg
	11853 FL K	solar flasher led lamp - red leds flash lens: Ø300 mm / material: PC / weight: 8.0 kg
	11850 FL S	solar flasher led lamp - yellow leds flash lens: Ø300 mm / material: PC / weight: 7.3 kg
	11852 FL K	solar flasher led lamp - red leds flash lens: Ø300 mm / material: PC / weight: 7.3 kg
	11862 FL S	led panel composite panel / reflective - yellow leds body: 40x40 cm / material: PC / weight: 7.0 kg
	11860 FL S	led panel composite panel / reflective - yellow leds body: 40x40 cm / material: PC / weight: 7.0 kg



AC Flasher Led Lamps & Signs

	PART No.	DESCRIPTIONS
	11882 FL A	led panel composite panel / reflective - yellow leds body: 40x40 cm / material: PC / weight: 2.8 kg
	11883 FL A	led panel composite panel / reflective - yellow leds body: 40x40 cm / material: PC / weight: 2.8 kg
	11885 FL A	AC flasher led lamp - yellow leds body: 40x40 cm / material: PC / weight: 3.1 kg
	11884 FL A	
	11888 FL A	led panel composite panel / reflective
	11889 FL A	body: 60x60 cm
	11886 FL A	material: PC - weight: 5.5 kg
	11890 FL A	




Product Technical Data


ELECTRONIC SPECS. (SOLAR)				
solar panel	type	glass laminated	color	Yellow Red
	dimension (H/L)	293x345 mm	dimension	Ø10-Ø5 mm
	voltage	18 V	flash rate	65 f/min
	watt	10 W	visibility dist.	500 m (night)
gel battery	material	SLA	operation time	whole night / daily sunlight
	voltage	12 V	operation temp.	-20°C/+60°C
	current	7.0 / 9.0 A/h		

ELECTRONIC SPECS. (AC)				
voltage	12 V AC	LED	color	yellow red white
	220 V AC		dimension	Ø10-Ø5 mm
			flash rate	65-54 f/min
			visibility dist.	500 m (night)
			operation temp.	-20°C/+60°C



Easy attached to Ø5.0 - Ø7.5 cm poles and can be adjustable on y-axis with the clamps







(60x60 cm)

Solar Flashing Led Road Maintenance Signs


PART No.	DESCRIPTIONS
11800 FL (SERIES)	led panel composite / reflective material body: PC - weight: 9.8 kg



(60x60 cm)

Solar Flashing Led Road Warning Signs

PART No.	DESCRIPTIONS
21800 FL (SERIES)	led panel composite / reflective material body: PC - weight: 9.8 kg



Product Technical Data



Easy attached to Ø5.0 - Ø7.5 cm poles and can be adjustable on y-axis with the clamps


ELECTRONIC SPECS.

solar panel	type	glass laminated	LED	color	red white
	dimension (H/L)	293x345 mm		dimension	Ø5 mm leds
	voltage	18 V		flash rate	54 f/min
	watt	10 W		visibility dist.	500 m (night)
gel battery	material	SLA	operation time	whole night/daily sunlight	
	voltage	12 V	operation temp.	-20°C/+60°C	
	current	7.0 / 9.0 A/h			




Solar Flashing Led Road Maintenance Signs

PART No.	DESCRIPTIONS
11700 S-LD (SERIES)	led panel composite / reflective material body: AL - weight: 16.5 kg




(100X100 cm)




Solar Flashing Led Road Warning Signs


PART No.	DESCRIPTIONS
11750 S-LD	led panel composite / reflective material body: AL - weight:14.0 kg
11700-EX-03	led panel composite / reflective material body: AL - weight: 16.5 kg



11750 S-LD (50x150 cm)



11700-EX-03 (100x100 cm)





12325 TK R2 12327 TK A R2




12393 TK R2 12395 TK A R2

90 cm PVC / TPE Cones

Reflective High Intensity Grade

	PART No.	DESCRIPTIONS
	12325 TK R2	PVC traffic cone - (H) 90 cm base:(\diamond) 38.5 cm / material: PVC / weight: 3.6 kg
	12327 TK A R2	PVC traffic cone - (H) 90 cm base:(\diamond) 48.5 cm / material: PVC / weight: 6.9 kg
	12393 TK R2	TPE traffic cone - (H) 90 cm base:(\diamond) 38.5 cm / material: TPE / weight: 3.0 kg
	12395 TK A R2	TPE traffic cone - (H) 90 cm base:(\diamond) 48.5 cm / material: TPE / weight: 6.3 kg

CONE - MOUNTED ACCESSORIES



12309 TK R2 12315 TK A R2



12387 TK R2 12389 TK A R2


75 cm PVC / TPE Cones

Reflective High Intensity Grade

	PART No.	DESCRIPTIONS
	12309 TK R2	PVC traffic cone - (H) 75 cm base:(\diamond) 38.5 cm / material: PVC / weight: 3.2 kg
	12315 TK A R2	PVC traffic cone - (H) 75 cm base:(\diamond) 48.5 cm / material: PVC / weight: 6.5 kg
	12387 TK R2	TPE traffic cone - (H) 75 cm base:(\diamond) 38.5 cm / material: TPE / weight: 2.7 kg
	12389 TK A R2	TPE traffic cone - (H) 75 cm base:(\diamond) 48.5 cm / material: TPE / weight: 6.0 kg



12306 TK R1 12326 TK A R1



12364 TK R1 12364 TK A R1

50 cm PVC / TPE Cones

Reflective High Intensity Grade

	PART No.	DESCRIPTIONS
	12306 TK R1	PVC traffic cone - (H) 50 cm base:(\diamond) 28.5 cm / material: PVC / weight: 1.3 kg
	12326 TK A R1	PVC traffic cone - (H) 50 cm base:(\diamond) 38.5 cm / material: PVC / weight: 2.65 kg
	12364 TK R1	TPE traffic cone - (H) 50 cm base:(\diamond) 28.5 cm / material: TPE / weight: 1.13 kg
	12364 TK A R1	TPE traffic cone - (H) 50 cm base:(\diamond) 38.5 cm / material: TPE / weight: 2.5 kg


70 / 52 / 50 cm PVC / TPE Cones

Reflective High Intensity Grade

	PART No.	DESCRIPTIONS
	12337 TK R2	PVC traffic cone - (H) 70 cm base:(Ø) 38 cm / material: PVC / weight: 2.3 kg
	12332 TK R2	PVC traffic cone - (H) 52 cm base:(Ø) 32 cm / material: PVC / weight: 1.25 kg
	12376 TK R2	TPE traffic cone - (H) 70 cm base:(Ø) 38 cm / material: TPE / weight: 1.9 kg
	12370 TK R2	TPE traffic cone - (H) 52 cm base:(Ø) 32 cm / material: TPE / weight: 1.0 kg
	12316 TK R2	PVC traffic cone - (H) 50 cm base:(Ø) 35 cm / material: PVC / weight: 1.7 kg




ACCESSORIES



90 / 50 / 32 cm PVC - 32cm TPE Cones

Reflective High Intensity Grade

	PART No.	DESCRIPTIONS
	12331 TK R2	PVC traffic cone - (H) 90 cm base:(Ø) 38.5 cm / material: PVC / weight: 4.0 kg
	12317 TK	PVC traffic cone - (H) 50 cm base:(Ø) 35 cm / material: PVC / weight: 1.8 kg
	12318 TK R1	PVC traffic cone - (H) 50 cm base:(Ø) 35 cm / material: PVC / weight: 1.8 kg
	12303 TK R1	PVC traffic cone - (H) 32 cm base:(Ø) 22 cm / material: PVC / weight: 0.65 kg
	12362 TK R1	TPE traffic cone - (H) 32 cm base:(Ø) 22 cm / material: TPE / weight: 0.54 kg




PVC - TPE Cones

Application


- * with premium quality stripes; high visibility
- * integral carrying handle and chain hole
- * lamp&signboard&chain can be attachable by cone adaptor(126 A)
- * with stackable feature; min. storage space
- * broad angled base provide wind resistance and stability

- * better visibility and long life color fading with UV protected bright orange color
- * operating temperature range: -20°C/+60°C
- * wide range of use: all warning-working zone and being managed dense traffic flow; including roads, construction areas, residential areas, parking lots and etc.






ACCESSORIES



PPC Cones

	PART No.	DESCRIPTIONS
	12322 TK R2	PPC cone - (H) 75 cm base:(∅) 40 cm / material: PPC / weight: 2.2 kg
	12320 TK A R2	PPC cone - (H) 75 cm base:(∅) 46 cm / material: PPC / weight: 4.9 kg
	12302 TK	PPC cone - (H) 50 cm base:(∅) 35 cm / material: PPC / weight: 0.90 kg



ACCESSORIES



Sign Board Cones

	PART No.	DESCRIPTIONS
	12300 TK	sign board cone - (H) 50 cm base:(∅) 35 cm / material: PPC / weight: 1.2 kg
	12301 TK A	sign board cone - (H) 52 cm base:(∅) 35 cm / material: PPC / weight: 4.0 kg
	12350 TK	sign board cone - (H) 60 cm base:(∅) 37 cm / material: PPC / weight: 1.4 kg
	12351 TK A	sign board cone - (H) 61.3 cm base:(∅) 37 cm / material: PPC / weight: 5.0 kg
	12352 TK A	sign board cone - (H) 61.3 cm base:(∅) 37 cm / material: PPC / weight: 5.0 kg

Pavement Signs & Foldable Floor Signs



	PART No.	DESCRIPTIONS
	12429 DB A	pavement sign - (HxW) 90x49 cm material: PPC / weight: 7.5 kg
	12426 DB A	pavement sign - (HxW) 90x49 cm material: PPC / weight: 7.5 kg
	12427 DB A	pavement sign - (HxW) 90x49 cm material: PPC / weight: 7.5 kg
	12424 DB R A	pavement sign - (HxW) 90x49 cm sign board: 60x40 cm / material: PPC / weight: 7.5 kg
	12421 DB R A	pavement sign - (HxW) 90x49 cm sign board: 60x40 cm / material: PPC / weight: 7.5 kg
	108 A F	foldable floor sign - (HxW) 62x24.5 cm sign board: 27x20 cm / material: ABS / weight: 1.0 kg
	107 A	foldable floor sign - (HxW) 62x24.5 cm material: ABS / weight: 1.0 kg

12429-12421-12426-12427-12424 DB R A / ACCESSORIES



Traffic Island Bollards

Reflective High Intensity Grade

	PART No.	DESCRIPTIONS
	12250 UB R	traffic island bollards - (HxØ) 100 cm x 300 mm(sign) fixing screw: 4x / material: TPU / weight: 3.25 kg
	12254 UB R	traffic island bollards - (HxØ) 90 cm x 200 mm(sign) fixing screw: 4x / material: TPU / weight: 2.00 kg
	12253 UB R	traffic island bollards - (HxØ) 75 cm x 100 mm(sign) fixing screw: 4x / material: TPU / weight: 1.40 kg
	22067 UB R	traffic island bollards - (HxØ) 45 cm x 100 mm(sign) fixing screw: 4x / material: TPU / weight: 0.95 kg



Flexible Removable Delineators

Reflective High Intensity Grade

	PART No.	DESCRIPTIONS
	12278 UB R	flexible removable delineator-TPU-(HxØ) 92 cm x 80 mm base: (Ø) 200 mm / fixing screw: epoxy / weight: 1.75 kg
	12232 UB R	flexible removable delineator-TPU-(HxØ) 75cm x 80mm base: (Ø) 200 mm / fixing screw: epoxy / weight: 1.48 kg
	12236 UB R	flexible removable delineator-TPU-(HxØ) 45 cm x 80 mm base: (Ø) 200 mm / fixing screw: epoxy / weight: 1.1 kg
	22076 UB R	flexible removable delineator-TPU-(HxØ) 45 cm x 80 mm base: (Ø) 200 mm / fixing screw: epoxy / weight: 1.1 kg
	22077 UB R	flexible removable delineator-TPU-(HxØ) 75 cm x 80 mm base: (Ø) 200 mm / fixing screw: epoxy / weight: 1.48 kg
	22078 UB R	flexible removable delineator-TPU-(HxØ) 92 cm x 80 mm base: (Ø) 200 mm / fixing screw: epoxy / weight: 1.75 kg



ACCESSORIES



TPU - Flexible Delineators With Socket


Reflective High Intensity Grade

	PART No.	DESCRIPTIONS
	12237 UB R	flexible delineator with socket - (HxØ) 75 cm x 110 mm base: (Ø) 260 mm / fixing screw: 4x / weight: 2.1 kg
	12249 UB R	flexible delineator with socket - (HxØ) 100 cm x 100 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 2.0 kg
	12243 UB R	flexible delineator with socket - (HxØ) 75 cm x 90 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 1.5 kg
	12247 UB R	flexible delineator with socket - (HxØ) 50 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 1.0 kg
	12281 UB R	flexible delineator with socket - (HxØ) 70 cm x 80 mm base: (Ø) 180 mm / fixing screw: 3x / weight: 1.0 kg
	12283 UB R	flexible delineator with socket - (HxØ) 40 cm x 80 mm base: (Ø) 180 mm / fixing screw: 3x / weight: 0.70 kg



ACCESSORIES





TPU - Flexible Delineators

Reflective High Intensity Grade


	PART No.	DESCRIPTIONS
	12211 UB R	flexible delineator - (HxØ) 100 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 1.60 kg
	12212 UB R	flexible delineator - (HxØ) 75 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 1.30 kg
	12214 UB R	flexible delineator - (HxØ) 45 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.98 kg
	12215 UB R	flexible delineator - (HxØ) 30 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.72 kg

ACCESSORIES



TPU - Flexible Delineators


Reflective High Intensity Grade



	PART No.	DESCRIPTIONS
	12288 UB R	flexible delineator - (HxØ) 100 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 1.60 kg
	12286 UB R	flexible delineator - (HxØ) 75cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 1.30 kg
	12284 UB R	flexible delineator - (HxØ) 45 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.98 kg
	12282 UB R	flexible delineator - (HxØ) 30 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.72 kg
	12245 UB R	flexible delineator - (HxØ) 30 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.72 kg
	12244 UB R	flexible delineator - (HxØ) 45 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.98 kg
	12242 UB R	flexible delineator - (HxØ) 75 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 1.30 kg
	12241 UB R	flexible delineator - (HxØ) 100 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 1.60 kg

TPU - TPE S - Flexible Delineators

Reflective High Intensity Grade



	PART No.	DESCRIPTIONS
	22036 UB R	flexible delineator - (HxØ) 100 cmx80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 1.60 kg
	22037 UB R	flexible delineator - (HxØ) 75 cmx80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 1.30 kg
	22038 UB R	flexible delineator - (HxØ) 45 cmx80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.98 kg
	22039 UB R	flexible delineator - (HxØ) 30 cmx80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.72 kg
	22024 UB R	TPE S flexible delineator - (HxØ) 30 cmx80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.54 kg
	22023 UB R	TPE S flexible delineator - (HxØ) 45 cmx80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.73 kg
	22022 UB R	TPE S flexible delineator - (HxØ) 75 cmx80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.95 kg
	22021 UB R	TPE S flexible delineator - (HxØ) 100 cmx80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 1.2 kg

TPE - Flexible Delineators

Reflective High Intensity Grade

	PART No.	DESCRIPTIONS
	22040 UB R	flexible delineator with socket - (HxØ) 100 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.94 kg
	22042 UB R	flexible delineator with socket - (HxØ) 75 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.73 kg
	22044 UB R	flexible delineator with socket - (HxØ) 45 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.49 kg
	12275 UB R	flexible delineator - (HxØ) 30 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.50 kg



ACCESSORIES



TPE - Flexible Delineators

Reflective High Intensity Grade


	PART No.	DESCRIPTIONS
	22048 UB R	flexible delineator with socket - (HxØ) 100 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.94 kg
	22050 UB R	flexible delineator with socket - (HxØ) 75 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.73 kg
	22052 UB R	flexible delineator with socket - (HxØ) 45 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.49 kg
	22019 UB R	flexible delineator - (HxØ) 30 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.50 kg
	22029 UB R	flexible delineator - (HxØ) 30 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.50 kg
	22053 UB R	flexible delineator with socket - (HxØ) 45 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.49 kg
	22051 UB R	flexible delineator with socket - (HxØ) 75 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.73 kg
	22049 UB R	flexible delineator with socket - (HxØ) 100 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.94 kg



TPE - Flexible Delineators

Reflective High Intensity Grade

	PART No.	DESCRIPTIONS
	22056 UB R	flexible delineator with socket - (HxØ) 100 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.94 kg
	22057 UB R	flexible delineator with socket - (HxØ) 75 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.73 kg
	22058 UB R	flexible delineator with socket - (HxØ) 45 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.49 kg
	22059 UB R	flexible delineator - (HxØ) 30 cm x 80 mm base: (Ø) 200 mm / fixing screw: 3x / weight: 0.50 kg
	12274 UB R	flexible delineator with socket - (HxØ) 40 cm x 80 mm base: (Ø) 180 mm / fixing screw: 3x / weight: 0.52 kg
	12272 UB R	flexible delineator with socket - (HxØ) 70 cm x 80 mm base: (Ø) 180 mm / fixing screw: 3x / weight: 0.74 kg



Channelizers With Delineator Reflective High Intensity Grade




12251 UB R

12268 UB R

12270 UB R

	PART No.	DESCRIPTIONS
	12251 UB R	channelizer with delineator - (HxLxW) 92x100x22 cm fixing screw: 6x / material:PPC-TPU / weight:4.6 kg
	12268 UB R	channelizer with delineator - (HxLxW) 75x100x22 cm fixing screw: 6x / material:PPC-TPU / weight:4.2 kg
	12270 UB R	channelizer with delineator - (HxLxW) 45x100x22 cm fixing screw: 6x / material:PPC-TPU / weight:3.8 kg

ACCESSORIES



Channelizers With Delineator Reflective High Intensity Grade




12297 UB R

12219 UB R


12218 UB R

	PART No.	DESCRIPTIONS
	12297 UB R	channelizer with delineator - (HxLxW) 92x100x20 cm fixing screw: 4x / material: PPC-TPU / weight: 4.8 kg
	12219 UB R	channelizer with delineator - (HxLxW) 75x100x20 cm fixing screw: 4x / material: PPC-TPU / weight: 4.5 kg
	12218 UB R	channelizer with delineator - (HxLxW) 45x100x20 cm fixing screw: 4x / material: PPC-TPU / weight: 4.1 kg

ACCESSORIES



Channelizers With Flap & Flexible Delineator Boards Reflective High Intensity Grade



12206 UB R

12207 UB R

22068 UB R



22066 UB R


12204 UB R

12203 UB R

	PART No.	DESCRIPTIONS
	12206 UB R	channelizer with flap - (HxLxW) 60x26x16 cm fixing screw: 2x / material: PPC-TPU / weight: 0.90 kg
	12207 UB R	channelizer with flap - (HxLxW) 30x26x16 cm fixing screw: 2x / material: PPC-TPU / weight: 0.75 kg
	22068 UB R	flexible delineator board(HxL)45x12 cm / base:(Ø)200mm fixing screw: 4x / material: TPU / weight: 0.95 kg
	22066 UB R	flexible delineator board(HxL)75x12 cm / base:(Ø)200mm fixing screw: 4x / material: TPU / weight: 1.4 kg
	12204 UB R	channelizer with flap - (HxLxW) 60x118x15 cm fixing screw: 3x / material: PPC-TPU / weight: 2.7 kg
	12203 UB R	channelizer with flap - (HxLxW) 30x118x15 cm fixing screw: 3x / material: PPC-TPU / weight: 2.5 kg

Channelizers With Flap & Cat Eyes


	PART No.	DESCRIPTIONS
	12266 UB R	channelizer with flap - (HxLxW) 66x100x22 cm fixing screw: 6x / material: PPC / weight: 3.6 kg
	12262 UB	channelizer with cat eyes - (HxLxW) 7.5x100x22 cm fixing screw: 6x / material: PPC / weight: 3.5 kg



12262 UB



12266 UB R

Panel Size: 57.5x13 cm - Reflective High Intensity Grade



Alternative 1 Alternative 2 Alternative 3 Alternative 4 Alternative 5

Channelizers Curbs



	PART No.	DESCRIPTIONS
	12202 UB	channelizer curb - (HxLxW) 4.8x118x15 cm fixing screw: 3x / material: PPC / weight: 2.3 kg
	12260 UB R	channelizer curb - (HxLxW) 6.0x100x15 cm fixing screw: 3x / material: PVC / weight: 6.0 kg



12260 UB R

12202 UB

Channelizers With Solar Flasher & Cat Eye


	PART No.	DESCRIPTIONS
	12220 UB	channelizer with solar flasher - (HxLxW) 8.0x100x20 cm fixing screw: 4x / material: PPC / weight: 3.7 kg
	12217 UB	channelizer with cat eye - (HxLxW) 8.0x100x20 cm fixing screw: 4x / material: PPC / weight: 4.1 kg




12217 UB

12220 UB


ELECTRONIC SPECS.					
solar panel	type	monocrystalline silicon cell	LED	color	Yellow Red
	dimension (H/L)	60x54 mm		dimension	Ø 5 mm leds
	voltage	3 V		flash rate	115 f/min
	watt	0.4 W		visibility dist.	100 m (night)
rechargeable battery	material	Ni-MH	operation time	whole night / daily sunlight	
	voltage	1.2 V	operation temp.	-20°C/+60°C	
	current	2000 mA/h			




11924 SL K



11926 SL S



11920 SL K



11922 SL S



11921 SL K



11923 SL S

Road Markers With Solar Flasher

	PART No.	DESCRIPTIONS
	11924 SL K	road marker with solar flasher - 145x125x28 mm material: AL / weight: 0.48 kg / fixing: epoxy glue
	11926 SL S	road marker with solar flasher - 145x125x28 mm material: AL / weight: 0.48 kg / fixing: epoxy glue
	11920 SL K	road marker with solar flasher - 145x125x28 mm material: AL / weight: 0.45 kg / fixing screw: 2x
	11922 SL S	road marker with solar flasher - 145x125x28 mm material: AL / weight: 0.45 kg / fixing screw: 2x
	11921 SL K	road marker with solar flasher - 135x120x28 mm material: AL / weight: 0.57 kg / fixing screw: 2x
	11923 SL S	road marker with solar flasher - 135x120x28 mm material: AL / weight: 0.57 kg / fixing screw: 2x

ELECTRONIC SPECS.

solar panel	type	monocrystalline silicon cell	LED	color	Yellow Red
	dimension (H/L)	60x54 mm		dimension	Ø 5 mm leds
	voltage	3 V		flash rate	115 f/min
	watt	0.4 W		visibility dist.	100 m (night)
rechargeable battery	material	Ni-MH	operation time	whole night/ daily sunlight	
	voltage	1.2 V	operation temp.	-20°C/+60°C	
	current	2000 mA/h			


Road Markers With Reflector



12005-2 YB



12005 YB



12000 YB



12006 YB



12002 YB



12003 YB

	PART No.	DESCRIPTIONS
	12005-2 YB	road marker with reflector - 100x100x21 mm material: ABS / weight: 0.15 kg / fixing screw: 2x
	12005 YB	road marker with reflector - 105x105x20 mm material: ABS / weight: 0.12 kg / fixing screw: 2x
	12000 YB	road marker with reflector - 125x150x32 mm material: PPC / weight: 0.20 kg / fixing screw: 4x
	12006 YB	road marker with reflector - 120x220x28 mm material: PPC / weight: 0.22 kg / fixing screw: 2x
	12002 YB	road marker with reflector - 120x120x28 mm material: PPC / weight: 0.18 kg / fixing screw: 4x
	12003 YB	road marker with reflector - 100x220x32 mm material: PPC / weight: 0.24 kg / fixing screw: 4x

Road Markers With Cat Eyes & Reflector



12011 YB




12007 YB



12009 YB



12004 YB



12123 YK




12124 YK

	PART No.	DESCRIPTIONS
	12011 YB	road marker with cat eyes - 100x102x10 mm material: AL / weight: 0.40 kg / fixing: epoxy glue
	12007 YB	road marker with cat eyes - 120x120x28 mm material: AL / weight: 0.30 kg / fixing screw: 2x
	12009 YB	road marker with cat eyes - 100x100x21 mm material: ABS / weight: 0.15 kg / fixing screw: 2x
	12004 YB	road marker with reflector - 140x120x25 cm material: PPC / weight: 0.12 kg / fixing screw: 4x
	12123 YK	road marker with reflector - (Ø) 250x35 mm material: PPC / weight: 0.45 kg / fixing screw: 4x
	12124 YK	road marker with reflector - (Ø) 250x35 mm material: PPC / weight: 0.45 kg / fixing screw: 4x


PVC Speed Ramps With Reflective Tapes & Reflector

PART No.	DESCRIPTIONS
12108 YK	speed ramps with reflective tapes - size:600x500x45 mm material: PVC-PPC / weight: 9.3 kg / fixing screw: 4x
12116 YK	speed ramps with reflective tapes - size:600x500x45 mm material: PVC-PPC / weight: 9.3 kg / fixing screw: 6x
12109 YK K	speed ramp end section - size:600x300x45 mm material: PVC-PPC / weight: 3.4 kg / fixing screw: 2x
12110 YK	speed ramps with reflective tapes - size:400x500x40 mm material: PVC-PPC / weight: 6.5 kg / fixing screw: 4x
12111 YK K	speed ramp end section - size:400x200x40 mm material: PVC-PPC / weight: 1.7 kg / fixing screw: 2x
12106 YK	speed ramps with reflector - size: 400x500x40 mm material: PVC-PPC / weight: 6.5 kg / fixing screw: 4x
12107 YK K	speed ramp end section - size: 400x200x40 mm material: PVC-PPC / weight: 1.7 kg / fixing screw: 2x




PPC Speed Bumps With Reflector

PART No.	DESCRIPTIONS
12102 YK	speed bump with reflector - size: 300x335x40 mm material: PPC / weight: 1.35 kg / fixing screw: 4x
12103 YK K	speed bump and section - size: 300x100x40 mm material: PPC / weight: 0.25 kg / fixing screw: 2x
12120 YK	speed bump with reflector - size: 250x500x35 mm material: PPC / weight: 1.15 kg / fixing screw: 4x
12121 YK K	speed bump and section - size: 250x120x35 mm material: PPC / weight: 0.26 kg / fixing screw: 2x
12100 YK	speed bump with reflector - size: 250x345x50 mm material: PPC / weight: 1.5 kg / fixing screw: 4x
12101 YK K	speed bump and section - size: 250x100x50 mm material: PPC / weight: 0.35 kg / fixing screw: 2x




PPC Speed Bumps With Solar Flasher & Cat Eyes


PART No.	DESCRIPTIONS
11938 SL	speed bump with solar flasher - size: 500x500x45 mm material: PPC / weight: 3.1 kg / fixing screw: 4x
11940 SL K	speed bump end section - size: 500x250x45 mm material: PPC / weight: 1.1 kg / fixing screw: 2x
12112 YK	speed bumps with cat eyes - size: 500x500x45 mm material: PPC / weight: 3.1 kg / fixing screw: 4x
12113 YK K	speed bump end section - size: 500x250x45 mm material: PPC / weight: 1.1 kg / fixing screw: 2x



11938 SL - ELECTRONIC SPECS.					
solar panel	type	monocrystalline silicon Cell	LED	color	Yellow Red
	dimension (H/L)	60x54 mm		dimension	Ø 5 mm leds
rechargeable battery	voltage	3 V		flash rate	120 f/min
	watt	0.4 W		visibility dist.	100 m (night)
	material	Ni-MH		operation time	whole night/ daily sunlight
	voltage	1.2 V		operation temp.	-20°C/+60°C
	current	2000 mA/h			




Car Parking Stoppers



	PART No.	DESCRIPTIONS
	12231 UB	car parking stopper - (HxL) 10x180 cm material: PPC / weight: 6.8 kg / fixing screw: 5x
	12233 UB	car parking stopper - (HxL) 10x110 cm material: PPC / weight: 4.3 kg / fixing screw: 3x
	12235 UB	car parking stopper - (HxL) 10x55 cm material: PPC / weight: 1.9 kg / fixing screw: 2x



Car Parking Stoppers



	PART No.	DESCRIPTIONS
	22231 UB R	car parking stopper - (HxL) 8.5x180 cm material: PPC / weight: 4.3 kg / fixing screw: 5x
	12216 UB R	car parking stopper - (HxL) 10x50 cm material: PVC / weight: 2.4 kg / fixing screw: 3x




Spike Barrier



	PART No.	DESCRIPTIONS
	12290 UB	spike barrier - size: 500x500x60 mm material: PPC-ST / weight: 7.3 kg / fixing screw: 6x
	12291 UB K	spike barrier end section - size: 500x90x60 mm material: PPC / weight: 0.70 kg / fixing screw: 2x

12290 UB (h6 x 50 x 50 cm)



Corner Guards




	PART No.	DESCRIPTIONS
	12292 UB R	corner guard - (H) 90 cm material: PVC / weight: 1.9 kg / fixing screw: 6x
	12295 UB R	corner guard - (H) 80 cm material: PVC / weight: 2.0 kg / fixing screw: 6x
	12294 UB R	corner guard - (H) 80 cm material: PVC / weight: 1.9 kg / fixing screw: 6x
	12296 UB R	corner guard - (H) 90 cm material: PVC / weight: 1.9 kg / fixing screw: 6x

Reflective Engineer Grade



Traffic Safety Mirrors

	PART No.	DESCRIPTIONS
	12226 TGA	traffic safety mirror - (Ø) 800 mm material: PPC / weight: 5.5 kg
	12227 TGA	traffic safety mirror - (Ø) 800 mm material: PPC / weight: 5.5 kg
	12228 TGA	traffic safety mirror - (Ø) 600 mm material: PPC / weight: 3.8 kg
	12229 TGA	traffic safety mirror - (Ø) 600 mm material: PPC / weight: 3.8 kg
	12248 TGA	traffic safety mirror - size: 600x800 mm material: ABS / weight: 6.0 kg
	12246 TGA	traffic safety mirror - size: 600x800 mm material: ABS / weight: 6.0 kg
	12267 TGA	traffic safety mirror - size: 400x600 mm material: ABS / weight: 3.3 kg
	12265 TGA	traffic safety mirror - size: 400x600 mm material: ABS / weight: 3.3 kg



Centrum Bollards


Reflective Engineer Grade



	PART No.	DESCRIPTIONS
	12213 UB R	centrum bollard -(HxØ)80x9.0 cm / base: (Ø)20 cm fixing screw: 4x / material: PPC / weight: 1.25 kg
	22035 UB R	centrum bollard -(HxØ)80x9.0 cm / base: (Ø)20 cm fixing screw: 4x / material: PPC / weight: 1.25 kg
	12223 UB R	centrum bollard -(HxØ)50x9.0 cm / base: (Ø)20 cm fixing screw: 4x / material: PPC / weight: 0.90 kg
	22031 UB R	centrum bollard -(HxØ)50x9.0 cm / base: (Ø)20 cm fixing screw: 4x / material: PPC / weight: 0.90 kg

Flexible Centrum Bollards

Reflective Engineer Grade




	PART No.	DESCRIPTIONS
	12276 UB D	flexible centrum bollard - (HxØ) 87x8 cm / base: (Ø)11cm fixing screw: 2x / material: TPU / weight: 1.72 kg
	12277 UB D	flexible centrum bollard - (HxØ) 68x8 cm / base: (Ø)11cm fixing screw: 2x / material: TPU / weight: 1.38 kg
	12279 UB D	flexible centrum bollard - (HxØ) 81.5x8 cm / base:(Ø)11cm fixing screw: 2x / material: TPU / weight: 1.62 kg
	12280 UB D	flexible centrum bollard - (HxØ) 62.5x8 cm / base:(Ø)11cm fixing screw: 2x / material: TPU / weight: 1.28 kg
	186 A	chain adaptor - (Ø) 60 mm material: PPC / weight: 0.007 kg
	188 A	bollards switch - (ØxH) 110mm x 0.3 cm material: metal / weight: 0.17 kg

ACCESSORIES



Ensign Centrum Bollards

Reflective Engineer Grade



	PART No.	DESCRIPTIONS
	22026 UB R	ensign centrum bollard - (H)120 cm panel size:(Ø)300mm fixing screw: 2x / material: TPU / weight: 2.1 kg
	22027 UB R	ensign centrum bollard - (H)102 cm panel size:(Ø)150 mm fixing screw: 2x / material: TPU / weight: 1.85 kg
	22028 UB R	ensign centrum bollard - (H)108cm panel size:210x125mm fixing screw: 2x / material: TPU / weight: 1.9 kg
	22032 UB R	ensign centrum bollard - (H)103cm panel size:100x400mm fixing screw: 2x / material: TPU / weight: 2.0 kg

Aluminum Composite Panel



Centrum Bollards

Reflective Engineer Grade

	PART No.	DESCRIPTIONS
	12205 UB R	centrum bollard - (H) 50 cm / base: 25x25 cm fixing screw: 4x / material: PE / weight: 1.5 kg
	22033 UB R	centrum bollard - (H) 50 cm / base: 25x25 cm fixing screw: 4x / material: PE / weight: 1.5 kg




22033 UB R




12205 UB R

Buffer & Steel Bollards

	PART No.	DESCRIPTIONS
	12285 UB PU	buffer bollard - (HxØ)78cmx150mm / base:Ø17x18cm material: PU / weight: 3.3 kg
	12289 UB ST	steel bollard - (HxØ)78cmx150mm / base:24x24cm fixing screw: 4x / material: ST / weight: 9.0 kg
	12293 UB ST	steel bollard - (HxØ)61cmx150mm / base:24x24cm fixing screw: 4x / material: ST / weight: 7.4 kg



12293 UB ST



12289 UB ST




12285 UB PU

Cable Protector Ramp


	PART No.	DESCRIPTIONS
	12298 UB	cable protector ramp - size: 600x500x75 mm fixing screw: 2x / material: PPC / weight: 8.7 kg
	12299 UB	cable protector ramp corner section-size:600x75 mm fixing screw: 2x / material: PPC / weight: 3.0 kg




12299 UB




12298 UB






PL 8010



PL 8011




PL 8012




PL 8013

Tactile Floor Indicators

	PART No.	DESCRIPTIONS
	PL 8010	tactile floor indicator - size: 40x40 cm material: TPU / weight: 0.70 kg
	PL 8011	tactile floor indicator - size: 40x40 cm material: TPU / weight: 0.70 kg
	PL 8012	tactile floor indicator - size: 40x40 cm material: TPU / weight: 0.85 kg
	PL 8013	tactile floor indicator - size: 40x40 cm material: TPU / weight: 0.85 kg



PL 8014



PL 8015




PL 8016




PL 8017

Tactile Floor Indicators

	PART No.	DESCRIPTIONS
	PL 8014	tactile floor indicator - size: 60x30 cm material: TPU / weight: 0.77 kg
	PL 8015	tactile floor indicator - size: 60x30 cm material: TPU / weight: 0.77 kg
	PL 8016	tactile floor indicator - size: 60x30 cm material: TPU / weight: 0.90 kg
	PL 8017	tactile floor indicator - size: 60x30 cm material: TPU / weight: 0.90 kg





PL 8018



PL 8019


Tactile Floor Indicators

	PART No.	DESCRIPTIONS
	PL 8018	tactile floor indicator - size: 58x58 cm material: TPU / weight: 1.40 kg
	PL 8019	tactile floor indicator - size: 58x58 cm material: TPU / weight: 1.40 kg



Reflective Sheeting Materials

PART No.	DESCRIPTIONS
HIP-9200	high intensity prismatic grade standard size: 123cmx45.7m/roll - white - digital printing
XW-1500	engineering grade standard size: 122cmx50m/roll - white - digital printing
XW-1500	engineering grade standard size: 122cmx50m/roll - yellow - red - blue
YSL-3102	commercial grade standard size: 122cmx50m/roll - white - digital printing
EX-3101	media grade standard size: 124cmx45.7m/roll - white - digital printing
EX-3100	media grade standard size: 124cmx45.7m/roll - white-yellow-red-blue



Reflective Tapes

PART No.	DESCRIPTIONS
ETR 5111	reflective tapes - 5 cmx10 m/roll - red - white
ETR 5112	reflective tapes - 10 cmx10 m/roll - red - white
ETR 5121	reflective tapes - 5 cmx10 m/roll - yellow - black
ETR 5122	reflective tapes - 10 cmx10 m/roll - yellow - black
ETR 5131	reflective tapes - 5 cmx10 m/roll - white
ETR 5141	reflective tapes - 5 cmx10 m/roll - yellow
ETR 5151	reflective tapes - 5 cmx10 m/roll - red
ETR 5161	reflective tapes - 5 cmx10 m/roll - blue




ETR 5122

ETR 5121

ETR 5112

ETR 5111



ETR 5161

ETR 5151

ETR 5141

ETR 5131



110 A



Alt. 1



Alt. 2



Alt. 3



111 A



Alt. 1



Alt. 2



Alt. 3



Alt. 4



Alt. 5



Alt. 6



196 A



Alt. 1



Alt. 2



Alt. 3



Alt. 4



Alt. 5



222 A R



Plastic Boards

Reflective Engineer Grade

	PART No.	DESCRIPTIONS
	110 A	plastic sign board - reflective size: 50 cm
	111 A	plastic sign board - reflective size: 40x34 cm
	196 A	plastic sign board - reflective size: Ø370 mm
	222 A R	traffic sign board - reflective size: Ø370 mm bi-directional sheeting

Plastic Boards



114 A



120 A



295 A F



124 A F

	PART No.	DESCRIPTIONS
	114 A	plastic sign board - size: 34x31 cm
	120 A	plastic sign board - size: Ø270 mm
	295 A F	traffic sign board - size: Ø370 mm bi-directional sheeting
	124 A F	traffic sign board - size: Ø270 mm bi-directional sheeting




Evelux Adaptors

	PART No.	DESCRIPTIONS
	194 A	delineator adaptor - (Ø) 80 mm
	126 A	cone adaptor - (H) 10.5 cm
	184 A	board adaptor - (Ø) 40mm
	174 A	threaded handle - Ø40 mm
	175 A	chain clip - Ø8 mm
	190 A	extra cone base - size: 38.5x38.5x5.0 cm - 5 kg



184 A



126 A



194 A



190 A



175 A



174 A

Barrier Accessories


	PART No.	DESCRIPTIONS
	128 A	8 mm chain - 25 m pk - red-white
	129 A	8 mm chain - 25 m pk - black-yellow
	127 A	8 mm chain - 3 m - red-white
	123 A	8 mm chain - 3 m - black-yellow
	152 A R	barricade profile for cones and posts - (L) 150 cm
	149 A	traffic sign barricade panel holder - size: 75x150 cm
	150 A	traffic sign barricade panel holder - size: 32x150 cm
	155 A	barricade holder's hook




149 A



150 A



129 A



128 A



155 A



127 A



123 A



152 A R

Fixing Screws

	PART No.	DESCRIPTIONS
	159 A	fixing anchor screw - Ø16x90 - Ø10x100 mm
	160 A	fixing anchor screw - Ø14x70 - Ø7.5x80 mm
	176 A	screw - Ø10x100 mm
	161 A	screw nail - Ø5.5x105 mm
	173 A	anchor - Ø14x70xØ8mm
	172 A	anchor - Ø16x90xØ10mm



176 A



160 A



159 A



172 A



173 A



161 A



EVELUX Trd.
Turkey-Istanbul Head Office

T: +90 212 210 07 42
M: sbozer@eveluxtech.com
A: Perpa Ticaret Mer. B Blok
Kat 2 No :31 Okmeydanı
İstanbul / TURKEY

EVELUXTECH Kft.
Budapest Warehouse

Mobile: + 36 30 970 5260
M: saleshu@eveluxtech.com
A: 2142 Nagytarcsa, Csonka
János utca 6/A
Budapest / HUNGARY

TEMKA GmbH
Europe Dist.

T: +49 9321/268 08 61
M: info@temka-gmbh.de
A: Steigweg 24
(Innopark, Geb. 63) 97318
Kitzingen / GERMANY

DNC Traffic
Romania Dist.

T: +40 799 934 049 / +40 723 165 809
M: sercandinc@dnc.ro
A: Strada Lizeanu Nr 26 , Sector 2
Bucharest / ROMANIA

ARBEL STRAUSS Parking
Israel Dist.

T: +972 4 911 3418
M: omri@arbelstrauss.com
A: Moshav Hibat Zion 3885
ISRAEL

BERRY Bldg. Mat. Trd.
Middle East Dist.

T: +971 4 234 8824
M: bayan@birigroup.com
A: Deera-Nakhel Road
Dubai / U.A.E

EVELUX Canada
Canada Dist.

T: (416) 845-7900
M: sales@eveluxcanada.ca
A: Markham, Ontario
Canada



1- TAVSİYE

Daha güvenli yollar oluşturmak için geniş ürün yelpazemiz sizin işlerinizi kolaylaştırır. **evelux** bayileri daha geniş bilgi almanız için size yardımcı olacaktır.

2- BELGELENDİRME

YÜKSELEN METAL TS EN ISO 9001:2015'e ve ISO 14001:2015' göre belgelendirilmiştir. Belgelendirme ürün kalitesi için istenilen çok çeşitli adımlara göre yapılmıştır. Dahası şirket içi işleyiş prosedürlerini geliştirmek için çalışanların sürekli eğitimini ve müşterilerimizle olan ilişkilerini güçlendirmeyi kapsar. Size en yüksek seviyede ki hizmeti sağlayabilmek bizim başarımızdır.

3- KATALOGLAR

Ana kataloğumuza ilave olarak; belediye, yol yapım firmaları, otopark yönetim çalışanları ve site yönetiminin kullanımı için özel ürün broşürü sunuyoruz. Lütfen bayilerimizden isteyiniz ya da online olarak görüntüleyiniz.

4- WEB SİTE

Web sayfamızı ziyaret ederek daha geniş ürün teknik özelliklerimizi inceleyebilirsiniz. e-teknik kataloğumuz dan kapsamlı fikir edinebilirsiniz. Kataloğtaki ölçüler teknik çizim değerleridir. Gerçek ürün üzerinden kontrolü sağlایınız. evelux.com.tr



Metal Kalıp Plastik San. Ltd. Şti.

Fabrika/Bayii Satış

(KOS) Kırım Cd.Sarı Çiçek Sk.No:3
Selçuklu 42250 KONYA/TÜRKİYE

☎ +90 332 248 10 73

☎ +90 332 251 81 65

✉ satis@eveluxtech.com

🌐 www.evelux.com.tr

EVELUX

Trafik Güvenlik Sis. Tic. A.Ş.

Dış Ticaret Müdürlüğü

Perpa Tic. Mer. B Blok 2. Kat No:31
Okmeydanı Şişli 34384 İSTANBUL/TÜRKİYE

☎ +90 212 210 07 42

☎ +90 212 210 07 22

✉ export@eveluxtech.com

🌐 www.eveluxtech.com

2023 Ürün Kataloğu

Katalogdaki tüm ürünler Yükselen Metal Kalıp Plastik ve Mak.San. Tic.Ltd.Şti. Ar&Ge departmanında geliştirilmiştir. Tasarımlar patentlidir. Devam eden ürün geliştirme programı nedeniyle, hammaddelerin belirli bir özelliğinden dolayı oluşabilecek toleranslara tabi olan özelliklerde, ekipmanda ve ürün/model kullanılabilirliğinde değişiklik yapma hakkı saklıdır.

evelux yükselengroup'un Tescilli Markasıdır.



14001:2015



TS EN ISO 9001:2015



TS EN 13422+A1



CE 200605

evelux.com.tr

Yetkili Bayi

